

Superspeed Rotors

# Thermo Scientific Fiberlite F10-6x500y Rotor

F10-6x500y



## ROTOR SPECIFICATIONS

Type	Fixed Angle
Material	Carbon Fiber Composite
Capacity	6 x 500 mL
Maximum Speed	10,000 rpm
Tube Dimensions Ø x L	70 x 160 mm
Angle	23°
K Factor	3413.0
Net Weight	12.7 kg/28 lbs
Warranty	15 years

	RCF	RADIUS
Maximum	17,700 xg	158.0 mm
Minimum	4,592 xg	41.0 mm

## ROTOR AND ACCESSORIES ORDERING INFORMATION

		THERMO SCIENTIFIC		BECKMAN®	HITACHI®
		SORVALL RC-6 Plus/Evolution RC/ RC-6/RC-5/RC-26/RC-2 Series	JOUAN KR22i Series	J2 Series/ Avanti Series	CR21/22 Series
Fiberlite F10-6x500y	Cat. No.	78510	096-062126	096-062114	096-062133
	Max. Speed	10,000 rpm	10,000 rpm	10,000 rpm	9,000 rpm
	Max. RCF	17,700 xg	17,700 xg	17,700 xg	14,300 xg
	Sample Containment <sup>1</sup>	ELC	ELC	ELC	

### Fiberlite F10-6x500y Rotor Package includes:

	Rotor Lid Assembly	099-062053	096-062126	099-062114	099-062133
	O-ring Refresher Kit <sup>2</sup>	021-062053	021-062126	021-062114	021-062133

## LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
500.0	450.0	Nalgene® PPCO Oak Ridge Bottle	3141-0500	24	6	10,000	17,700	70 x 160	Closure	Included	24	PP Sealing
500.0	450.0	Nalgene PC Oak Ridge Bottle	3140-0500	24	6	10,000	17,700	70 x 160	Closure	Included	24	PP Sealing
250.0	—	Corning® Disposable Conical Tube <sup>3</sup>	—	—	6	10,000	17,700	—	Adapter	010-1135	2	1 place/adapter
250.0	250.0	Nalgene PPCO Oak Ridge Bottle	3141-0250	36	6	10,000	17,700	61 x 133	Closure Adapter	Included 010-0151	36 2	PP Sealing 1 place/adapter
250.0	250.0	Nalgene PC Oak Ridge Bottle	3140-0250	36	6	10,000	17,700	61 x 135	Closure Adapter	Included 010-0151	36 2	PP Sealing 1 place/adapter

PERFECT FIT: FREE SET OF NALGENE PRODUCTS INCLUDED WITH ROTOR PURCHASE

<sup>1</sup> Sample containment may vary by rotor. ELC denotes Enhanced Liquid Containment.

<sup>2</sup> Includes 5 O-rings, 3 O-ring Grease Packets and 4 oz FiberClene Lab Cleaner (017-0024).

<sup>3</sup> Performance depends upon tube brand. Contact your sales representative for recommended tube manufacturers and further information.

## LABWARE ORDERING INFORMATION CONTINUED

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
175.0	175.0	Nalgene PPCO Conical Wide-Mouth Tube	3143-0175	36	6	10,000	17,700	61 x 144	Closure Adapter	Included	36	PP Sealing
										010-0152	2	1 place/adapter
175.0	175.0	Nalgene PC Conical Wide-Mouth Tube	3144-0175	36	6	10,000	17,700	61 x 144	Closure Adapter	Included	36	PP Sealing
										010-0152	2	1 place/adapter
80.0	73.0	PC Oak Ridge Tube	010-0515	6	6	10,000	17,700	38 x 109	Closure Adapter	Included	6	PP Sealing
										010-1114	2	1 place/adapter
80.0	76.0	PPCO Oak Ridge Tube	010-1280	6	6	10,000	17,700	38 x 109	Closure Adapter	Included	6	PP Sealing
										010-1114	2	1 place/adapter
85.0	81.0	Nalgene PC Oak Ridge Tube	3118-0085	100	6	10,000	17,700	38 x 109	Closure Adapter	Included	100	PP Screw Top
										010-1114	2	1 place/adapter
50.0	50.0	Nunc™ Disposable Conical Tube	334959	25	6	9,000	14,300	30 x 115	Closure Adapter	Included	25	PP Sealing
										010-1102	2	1 place/adapter
50.0	–	Corning Disposable Conical Tube <sup>3</sup>	–	–	6	9,000	14,300	–	Adapter	010-1102	2	1 place/adapter
50.0	–	BD Falcon® Disposable Conical Tube <sup>3</sup>	–	–	6	9,000	14,300	–	Adapter	010-1102	2	1 place/adapter
50.0	46.0	Nalgene PC Oak Ridge Tube	3138-0050	50	12	10,000	17,700	29 x 108	Closure Adapter	Included	50	PP Sealing
										010-1112	2	2 places/adapter
50.0	46.0	Nalgene PPCO Oak Ridge Tube	3139-0050	50	12	10,000	17,700	29 x 108	Closure Adapter	Included	50	PP Sealing
										010-1112	2	2 places/adapter
50.0	46.0	Nalgene PSF Oak Ridge Tube	3137-0050	50	12	10,000	17,700	29 x 108	Closure Adapter	Included	50	PP Sealing
										010-1112	2	2 places/adapter
50.0	46.0	Nalgene FEP Oak Ridge Tube	3114-0050	10	12	10,000	17,700	29 x 108	Closure Adapter	Included	10	ETFE Screw Cap
										010-1112	2	2 places/adapter
30.0	30.0	Nalgene PC Oak Ridge Tube	3138-0030	50	18	10,000	17,700	26 x 102	Closure Adapter	Included	50	PP Sealing
										010-1115	2	3 places/adapter
30.0	30.0	Nalgene PPCO Oak Ridge Tube	3139-0030	50	18	10,000	17,700	26 x 102	Closure Adapter	Included	50	PP Sealing
										010-1115	2	3 places/adapter
30.0	30.0	Nalgene PSF Oak Ridge Tube	3137-0030	50	18	10,000	17,700	26 x 102	Closure Adapter	Included	50	PP Sealing
										010-1115	2	3 places/adapter
30.0	30.0	Nalgene FEP Oak Ridge Tube	3114-0030	50	18	10,000	17,700	26 x 102	Closure Adapter	Included	50	ETFE Screw Cap
										010-1115	2	3 places/adapter
16.0	16.0	Nalgene PC Oak Ridge Tube	3139-0016	50	42	10,000	17,700	18 x 107	Closure Adapter	Included	50	PP Sealing
										010-1105	2	7 places/adapter
16.0	16.0	Nalgene PPCO Oak Ridge Tube	3138-0016	50	42	10,000	17,700	18 x 107	Closure Adapter	Included	50	PP Sealing
										010-1105	2	7 places/adapter
15.0	–	Corning Disposable Conical Tube <sup>3</sup>	–	–	36	–	–	–	Adapter	010-1099	2	6 places/adapter
15.0	–	BD Falcon Disposable Conical Tube <sup>3</sup>	–	–	36	–	–	–	Adapter	010-1099	2	6 places/adapter
10.0	8.0	Nalgene PPCO Oak Ridge Tube	3139-0010	50	42	10,000	17,700	16 x 100	Closure Adapter	Included	50	PP Sealing
										010-1308	2	7 places/adapter
10.0	8.0	Nalgene PC Oak Ridge Tube	3138-0010	50	42	10,000	17,700	16 x 100	Closure Adapter	Included	50	PP Sealing
										010-1308	2	7 places/adapter
10.0	–	Vacutainer® Tube <sup>3</sup>	–	–	42	–	–	16 x 100	Adapter	010-1103	2	7 places/adapter
3.0	–	Vacutainer Tube <sup>3</sup>	–	–	84	–	–	10 x 64	Adapter	010-1137	2	14 places/adapter

<sup>3</sup> Performance depends upon tube brand. Contact your sales representative for recommended tube manufacturers and further information.

Note: Thermo Scientific Sorvall RC-6 Plus centrifuges manufactured prior to March 2009 may require software upgrade 314295G01 (NA) or HKKS308102E (Europe and Asia Pacific).

© 2010 Thermo Fisher Scientific Inc. All rights reserved. Beckman is a registered trademark of Beckman Coulter Inc. Hitachi is a registered trademark of Nissei Sangyo America. Corning is a registered trademark of Corning Inc. BD Falcon and Vacutainer are registered trademarks of BD Bioscience. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit  
[www.thermoscientific.com/rotors](http://www.thermoscientific.com/rotors)

**Thermo**  
 SCIENTIFIC